

NEWS / HOME

Products

Single Shut-Off Double Shut-Off Safety Thermoplastic Water Applications RectuKey TEMA

System Components

History

NYCOIL

Representatives

Jobs

Contact

Search

Press

Blow-gun technology

Short nozzle

Directed air jet. Ideal for blowing out blind holes and work pieces.

Safety nozzle

with center bore and lateral annular gap. In blowing operation, a protective shield is formed against rebounding shavings. The noise level is also significantly reduced. When the center bore is held closed, the air escapes through the annular gap.

Extension pipe

made of aluminium, therefore rustproof.For blowing out deep holes and in inaccessible locations.

Protective shield

is mounted behind the nozzle being used. Prevents shavings from rebounding.

Venturi nozzle

saves energy, since 2/3 of the surrounding air is sucked in thanks to the Venturi principle. Wide blow-out effect thanks to the large nozzle effect. When the nozzle hole is held closed, the air escapes through the lateral holes.

Nozzle with sintered metal insert

Low noise level (63 - 73 dB (A)) yet with exceedingly good blowout performance (up to 380 i/min).



AS 06 TF

AS09TF

AS21SF

AS26SF

6 mm 9 mm

Plug NW 5

Plug NW 7,2

AJ 13-Set	Connection	Extension Tube	part number				
	G 1/4 i.	6 mm bent	AJ13/06SET				
including 10 Blow Guns AJ 13	G 1/4 i.	8 mm bent	AJ13/08SET				
AK 13-Set	Connection	Extension Tube	part number				
including 10 Blow Guns AK 13	G 1/4 i.		AK 13 SET				
Blow Gun	Connection	part number					
		G 1/4 i.	AA13				
		6 mm	AA06TF				
		9 mm	AA09TF				
		Plug NW 5	AA21SF				
made of Aluminium, with standard n	Plug NW 7,2	AA26SF					
Blow Gun		Connection	part number				
		G 1/4 i.	AS13				

made of Aluminium, with safety nozzle

11 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1							
Blow Gun			Connection		part number		
			G 1/4 i.		AR13		
		6 mm		AR06TF			
		9 mm			AR09TF		
made of Aluminium, with sintered metal insert			Plug NW 5		AR21SF		
			lug NW 7,	2	AR26SF		
Plow Gun	1	Con	noction		port number		
Blow Gun		Connection G 1/4 i.			part number AV13		
		6 mm		AV13 AV06TF			
		9 mm		AV09TF			
		Plug NW 5		AV21SF			
made of Aluminium, with extension tube			Plug NW 7,2		AV26SF		
Blow Gun			Connection		part number		
		G 1/4 i.			AT3		
		6	mm		AT06TF		
		9	mm		AT09TF		
		Plug NW 5			AT21SF		
made of Aluminium, with Venturi nozzle		Plug NW 7,2			AT26SF		
			Connection		nort number		
Blow Gun		Connec		JUII	part number		
made of Aluminium, lever operated with safety nozzle			1/4NPSF		ASG-1		
Plant Cup		Compostion			nort number		
Blow Gun		Connection		part number			
	G 1/4 i.		l	AN13			
	6 mm		AN06TF				
	9 mm		AN09TF				
made of impact registent plactic	F	Plug NW 5		AN21SF			
with standard nozzle			-				
fixed nozzle, impossible to replace			Plug NW 7,2 AN26SF				
Blow Gun			Connection part number				
made of impact resistant plastic with standard nozzle fixed nozzle, impossible to replace		G 1/4 i.		AL13			
		6 mm		AL06TF			
		9 mm		AL09TF			
		Plug NW 5		AL21SF			
		Plug NW 7,2		AL26SF			
Blow Gun (Connection		part number			
		G 1/4 i.		AF13			
	6 mm			AF06TF			
)			ALOUTI		

- Schnellverschluss-Kupplungen,Quick Connect Couplings,Pne	umatik,Hydr	aulik					
		9	mm		AF09TF		
		Plug	NW 5		AF21SF		
made of impact resistant plastic			NW 7,2		AF26SF		
with sintered metal insert							
Blow Gun		Co	onnection	T	part number		
made of impact resistant plastic with aluminium extension tube fixed nozzle, impossible to replace			G 1/4 i.		AK13		
			6 mm		AK06TF		
			9 mm		AK09TF		
			ug NW 5		AK21SF		
			ıg NW 7,2		AK26SF		
Blow Gun		I C	onnection		part number		
			G 1/4 i.		AZ13		
			6 mm		AZ06TF		
made of impact resistant plastic extension tube brass			9 mm		AZ09TF		
nickel plated with a star tip nozzle - meets OSHA standards			Plug NW 5		AZ21SF		
 light weight rugged extension tube fixed nozzle, impossible to replace 		PI	ug NW 7,2		AZ26SF		
Blow Gun		l c	onnection		part number		
			G 1/4 i.		AC13		
				_			
,			6 mm		AC06TF		
made of impact resistant plastic			9 mm		AC09TF		
extension tube brass nickel plated		Plug NW 5			AC21SF		
 rugged extension tube fixed nozzle, impossible to replace 		PI	ug NW 7,2		AC26SF		
Blow Gun	Conn	ection	Connection	on part number			
		/4 i.			AX13		
	6 mm				AX06TF		
	9 mm				AX09TF		
	Plug NW 5				AX21SF		
made of impact resistant plastic with Venturi nozzle	Plug	Plug NW 7,2			AX26SF		
Play Con	1	Com	Converties		nort accept a		
Blow Gun		Connection G 1/4 i.			part number Al13		
			mm		AI06TF		

- Schnellverschluss-Kupplungen,Quick Connect Couplings,Pneumatik,Hydra	ılik						
		9 mm			AI09TF		
	Plu	ıg NW 5		Al21SF			
made of impact resistant plastic	Plu	g NW 7,2		Al26SF			
with R 1/8" i. without nozzle							
Blow Gun	0-						
Blow Gun		nnection 3 1/4 i.	part number AM13				
		6 mm		AM06TF			
		9 mm		AM09TF			
made of impact resistant plastic		Plug NW 5		AM21SF			
with M 12 x 1,25 IG	Plu	g NW 7,2		AM26SF			
Blow Gun		Connection		part number			
		G 1/4 i.		AJ13/06B			
		G 1/4 i.		AJ13/08			
		G 1/4 i.	AJ13/08B				
\ `		G 1/4 i.	AJ13-300				
made of red impact resistant plastic with aluminium extension tube		G 1/4 i.		AJ13-500 AJ13-1000			
Standard Nozzle Co			part number				
for Blow Gun made of Aluminium	M 12 x 1,2			KD12			
Safety Nozzle			Connection part number				
for Blow Gun made of Aluminium With center bore/lateral annular gap. In blowing operation a protection shield against kicking chips is formed, and noice level is clearly reduced. When center bore is held locked, air escapes through annular gap				x 1,25	SD12		
Extension Tube, 150 mm long			ion part number				
for Blow Gun made of Aluminium For blowing-out deep holes and blind spots.	M 12 x 1,25 VR12			VR12			
Venturi-Nozzle Connection part number							
Venturi-Nozzie Connection part number							



M 12 x 1,25

AT12

Energy saving as 2/3 of environmental air is aspirated due to the Venturi principle. Wide blowout effect due to high nozzle performance. When the center bore is held locked, air escapes through the lateral holes.